## TL-WR841N v13 – Hotspot Router – DHCP

Minimum Firmware version date code (170814)

- 1. Connect power to the router and turn it on.
- 2. Connect a computer to the router with either:
  - a. An Ethernet cable to a yellow port.
  - b. The WiFi info on the bottom of the router.



3. Open browser and go to tplinkwifi.net Login with username: "admin" and password "admin"




 On Quick Setup – Start, hit Next. (If the Quick Setup isn't showing, hit Quick Setup on the left.)

Ptp-link	TP-Link Wireless N Router WR841N Model No. TL-WR841N
Status	
Quick Setup	
Operation Mode	Quick Setup - Start
Network	
Wireless	
Guest Network	Run the Quick Setup to manually configure your internet connection and wireless setting To continue, please click the Next button.
DHCP	To exit, please click the Exit button.
Forwarding	
Security	
Parental Controls	Exit Next
Access Control	

 On Quick Setup – Operation Mode, choose Hotspot Router and hit Next.



 On Quick Setup – WAN Connection Type, choose Dynamic IP and hit Next.



7. On AP List, look through the SSID column for

## and click on Connect for that row.

	The scanned APs are					
	AP numbers: 11	Refresh				
ID	BSSID	SSID	Signal strength	Channel	Encryption	Connect
1	00:13:92:60:08:50	Cactus-Wireless_WPA	86	11	WPA-PSK/TKIP	Connect
2	00:13:92:E0:08:50	Cactus_Hotspot_IA	86	11	WPA2-PSK/AES	Connect
3	00:13:92:A0:08:50	Cactus_Hotspot_PPPoE	86	11	None	Connect
4	00:13:92:20:08:50	Cactus_Hotspot_WEP	86	11	Open System/WEP	Connect
5	D4:6E:0E:F8:40:2E	PCRE_2	67	4	WPA2-PSK/AES	Connect
6	10:9F:A9:15:7C:ED	PCRE	62	11	WPA2-PSK/AES	Connect
7	C0:25:E9:5F:04:84	NaturistStudio	60	4	WPA2-PSK/AES	Connect
8	66:D1:54:77:EE:C1	Colter's Creek - Guests	57	1	WPA2-PSK/AES	Connect
9	28:CF:DA:B1:CF:BD	FRATMIKE	51	11	WPA2-PSK/AES	Connect

## 8. In the Client Setting section:

- a. Double check the SSID
- b. If the network you are connecting to is secured, enter the Wireless Pasword.

lient Setting	
SSID(to be bridged):	Cactus-Wireless_WPA
MAC Address(to be bridged):	00:13:92:60:08:50 e.g. 00:1D:0F:11:22:33
	Scan
Key Type:	WPA-PSK 🗸
Encryption:	TKIP
Wireless Password:	

## TL-WR841N v13 – Hotspot Router – DHCP

Minimum Firmware version date code (170814)

- 9. Scroll down to the AP Setting section:
  - a. Make up your own wireless network name and password.
  - b. Enter them in Local Network SSID and Wireless Password.
  - c. Hit Next.

Key Type:	Scan Vo Security V
	No Security
AP Setting	
Local Network SSID:	TP-Link_D798
Security:	
۲	WPA2-PSK (Recommended)
	Wireless Password 36517237
	(Enter ASCII characters between 8 and 63 or Hexadecimal characters between 8 and 64.)
0	Disable Wireless Security
	Back Next

10. Review your choices and hit the Finish button at the

	ettings			
	Operation Mode:	Hotspot		
	Wireless Channel:	11		
	Wireless Network Name(SSID):	TP-Link_D798		
	Wireless Security Mode:	WPA2-PSK		
	Wireless Password:	36517237		
AN Settin	05			
LAN Settin	gs Default Access:	http://tplinkwifi.net		
LAN Settin		http://tplinkwifi.net Static IP		
LAN Settin	Default Access:			